



**SOLD SEPARATELY  
PLUGS, CONTACTS & ACCESSORIES**

ACCESSORY	PART NUMBER
AIR SIDE PLUG	FP39751
VACUUM SIDE PLUG	FA39111
PLASTIC BACK SHELL (AIR SIDE)	FP16883
METAL BACK SHELL (VAC SIDE)	FA19847
CONTACT 12 AWG (20 AMP)	FP39118
CONTACT 16 AWG (10 AMP)	FP39118-02
CONTACT CRIMP TOOL	FP39756
CRIMP LOCATOR	FP39764
CONTACT REMOVAL TOOL	FP39757

PERFORMANCE SPECIFICATIONS	
VOLTAGE	500V DC
CURRENT	20 AMPS
TEMPERATURE WITHOUT PLUGS	-269°C TO 350°C

LEAK RATE <1 X 10E-10 ATM-CC/SEC (He)

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE <b>3 PIN SUB D POWER CONNECTORS</b>			
REV.	APP'D	DATE	SCALE 4:5	DIMENSIONS IN INCHES [mm]	DRAWN	JF	8/3/2020	PART NO. FA41213 REV. A WWW.SOLIDSEALING.COM	
A2	JF	11/11/2020	MPC10698-11		ENG APPR.	JF	8/3/2020		

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**