



+ CONDUCTOR LOCATIONS: A,C,E,G,J
 - CONDUCTOR LOCATIONS: B,D,F,H,K

PLUGS SOLD SEPARATELY:
 -AIR SIDE PLUG W/CRIMP CONTACTS: FA41398
 -VACUUM SIDE PEEK PLUG: FA41399

PERFORMANCE SPECIFICATIONS	
CONDUCTOR MATERIAL:	(+) CHROMEL / (-) ALUMEL
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 5 PAIR T/C TYPE K CONNECTOR					
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	9/4/2020	PART NO. FA41237 REV. A		WWW.SOLIDSEALING.COM	
A1	JF	9/8/2020	MPCL0055-21SL		ENG APPR.	JF	9/8/2020			SALES DWG NO. FA41237SL REV. A1	

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.