



- + CONDUCTOR LOCATIONS: A,C,E,G,J,L,N,R,T,V,X,Z,b,d,f,h
- CONDUCTOR LOCATIONS: B,D,F,H,K,M,P,S,U,W,Y,a,c,e,g,j

PLUGS SOLD SEPARATELY:
 - AIR SIDE PLUG W/CRIMP CONTACTS: FA19814
 - VACUUM SIDE PEEK PLUG: FA19815

PERFORMANCE SPECIFICATIONS	
CONDUCTOR MATERIAL:	(+)CHROMEL / (-)ALUMEL
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 16 PAIR T/C TYPE K CONNECTOR					
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	9/8/2020	PART NO. FA41238 REV. A		WWW.SOLIDSEALING.COM	
A1	JF	9/8/2020	MPCL0253-12SL		ENG APPR.	JF	9/8/2020			SALES DWG NO. FA41238SL REV. A1	

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.