



CRIMP CONTACT MATERIAL:	LOCATIONS:
CHROMEL (+)	A,C,E
ALUMEL (-)	B,D,F

PERFORMANCE SPECIFICATIONS	
THERMOCOUPLE:	TYPE K
TEMPERATURE:	-55°C TO 200°C

REFER TO INSTRUCTION SHEET "NS41396" FOR PLUG ASSEMBLY INSTRUCTIONS.

<p>PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.</p>				<p>THIRD ANGLE PROJECTION</p> 		<p>TITLE</p> <p>TYPE K 3 PAIR AIR SIDE PLUG</p>				 <p>SOLID SEALING TECHNOLOGY</p>	
REV.	APP'D	DATE	SCALE 2.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	9/8/2020	PART NO. FA41396 REV. A	WWW.SOLIDSEALING.COM		
A2	JF	06/30/2021	MSMM0026-31		ENG APPR.	JF	9/8/2020		SALES DWG NO. FA41396SL REV. A2		

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.