



CRIMP CONTACT MATERIAL:	LOCATIONS:
CHROMEL (+)	A,C,E
ALUMEL (-)	B,D,F

PERFORMANCE SPECIFICATIONS	
THERMOCOUPLE:	TYPE K
TEMPERATURE:	-55°C TO 200°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE TYPE K 3 PAIR AIR SIDE PLUG			
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	9/8/2020	PART NO. FA41396 REV. A	WWW.SOLIDSEALING.COM
A1	JF	9/8/2020	MSMM0026-31		ENG APPR.	JF	9/8/2020		SALES DWG NO. FA41396SL REV. A1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.