



|                         |            |
|-------------------------|------------|
| CRIMP CONTACT MATERIAL: | LOCATIONS: |
| CHROMEL (+)             | A,C,E,G,J  |
| ALUMEL (-)              | B,D,F,H,K  |

|                            |                |
|----------------------------|----------------|
| PERFORMANCE SPECIFICATIONS |                |
| THERMOCOUPLE:              | TYPE K         |
| TEMPERATURE:               | -55°C TO 200°C |

REFER TO INSTRUCTION SHEET "NS41398" FOR PLUG ASSEMBLY INSTRUCTIONS.

|  |       |            |             |                            |           |                                      |          |   |  |
|--|-------|------------|-------------|----------------------------|-----------|--------------------------------------|----------|---|--|
| PROPRIETARY AND CONFIDENTIAL<br>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED. |       |            |             | THIRD ANGLE PROJECTION<br> |           | TITLE<br>TYPE K 5 PAIR AIR SIDE PLUG |          |   |  |
| REV.   | APP'D | DATE       | SCALE 2:1   | DIMENSIONS IN INCHES [mm]  | DRAWN     | JF                                   | 9/8/2020 | PART NO. FA41398 REV. A<br>WWW.SOLIDSEALING.COM |  |
| A2   | JF    | 06/30/2021 | MSMM0021-21 |                            | ENG APPR. | JF                                   | 9/8/2020 |   |  |

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**