



PLUG SOLD SEPERATELY:
 -PEEK PLUG FA41187 FOR USE ON BOTH SIDES
 -EXTRA CRIMP CONTACTS KT14601

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500V DC
CURRENT:	5 AMPS*
PRESSURE:	0 PSIG @ 20°C**
TEMPERATURE:	-25°C TO 205° C

*CURRENT PER PIN MAX @ 20°C
 (UP TO 20% TOTAL NUMBER OF PINS)

**FOR INTERNAL PRESSURE 5 TO 100 PSIG
 AN OVERPRESSURE RING IS REQUIRED.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 9 PIN SUB-C CONNECTOR			
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	12/22/2020	PART NO. FA41821 REV. A	WWW.SOLIDSEALING.COM
A3	JF	1/14/2021	MPCL0697-21		ENG APPR.	JF	12/22/2020		SALES DWG NO. FA41821SL REV. A3

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.