



PERFORMANCE SPECIFICATIONS	
VOLTAGE DWV:	50KV DC
PRESSURE:	180-200 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE SAPPHIRE ISOLATOR			
REV.	APP'D	DATE	SCALE 1.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	1/13/2021	PART NO. FA41847 REV. A	WWW.SOLIDSEALING.COM
A1	JF	11/30/2021	BRCL0081-31		ENG APPR.	JF	11/30/2021		SALES DWG NO. FA41847SL REV. A1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.