



PLUG SOLD SEPERATELY:
 -PEEK PLUG FA41187 FOR USE ON BOTH SIDES
 -EXTRA CONTACTS KT14601

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500V DC
CURRENT:	5 AMPS*
TEMPERATURE:	-269°C TO 450°C

*CURRENT PER PIN MAX @ 20°C
 (UP TO 20% TOTAL NUMBER OF PINS)

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 9 PIN SUB-C CONNECTOR			
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	CW	1/21/2021	PART NO. FA41894 REV. A	WWW.SOLIDSEALING.COM
A1	CW	1/21/2021	MPCL0712-11		ENG APPR.	JF	1/21/2021		SALES DWG NO. FA41894SL REV. A1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.