


PART NO.	AIR SIDE PLUG
FA42122	NO
KT42122	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500V DC
CURRENT:	0.8 AMPS
PRESSURE:	1400 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 350°C
TEMPERATURE WITH PLUG:	-65°C TO 165°C

PROPRIETARY AND CONFIDENTIAL  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE  
 50 OHM BNC CONNECTOR



REV.	APP'D	DATE	SCALE 4:1	DIMENSIONS IN INCHES [mm]	DRAWN	CW	3/2/2021
A1	CW	3/2/2021	COBN0044-12		ENG APPR.	JF	3/2/2021

PART NO. FA42122 REV. A

WWW.SOLIDSEALING.COM

SALES DWG NO. FA42122SL REV. A1

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**