




PART NO.	CABLE LENGTH
FA42314	48"
FA42314-02	96"

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	250V DC
CURRENT:	3 AMPS
TEMPERATURE:	-55°C TO 200°C


PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				 THIRD ANGLE PROJECTION		TITLE MICRO C, 7 PIN VACUUM PLUG CABLE ASSEMBLY			 SOLID SEALING TECHNOLOGY	
REV.	APP'D	DATE	SCALE 3:1	DIMENSIONS IN INCHES [mm]	DRAWN	CW	4/15/2021	PART NO. (SEE TABLE) REV. A	WWW.SOLIDSEALING.COM	
A1	JF	04/20/2021	MSMM0128-11		ENG APPR.	JF	04/20/2021		SALES DWG NO. FA42314SL REV. A1	

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.


3 PINS



HERMETIC
FEEDTHRU
FA42916
(LASER WELD ONLY)




PLUG
FA42930*




PRE-WIRED PLUG
-KAPTON: FA43039
-PTFE: FA43040


7 PINS




HERMETIC
FEEDTHRU
FA41283



PLUG
FA41289*




IN-VAC
RECEPTACLE
FA42367




PRE-WIRED PLUG
-KAPTON: FA42314
-PTFE: FA42315


19 PINS




PLUG
FA41232*



HERMETIC
FEEDTHRU
FA41401




IN-VAC
RECEPTACLE
FA41656




PRE-WIRED PLUG
-KAPTON: FA42316
-PTFE: FA42317


55 PINS




PLUG
FA42256*



HERMETIC FEEDTHRU
FA42250



IN-VAC
RECEPTACLE
FA42375




PRE-WIRED PLUG
-KAPTON: FA42318
-PTFE: FA42319

***CONTACTS NOT INCLUDED**

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE
SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN
PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE
PROJECTION



TITLE

MICRO SERIES FAMILY



SOLID SEALING
TECHNOLOGY

REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN	DRAWN	HJ	04/09/2021
A2	CW	4/21/2022	MPC10735-11	INCHES [mm]	ENG APPR.	HJ	05/03/2021


REV: A2

WWW.SOLIDSEALING.COM


SALES DWG NO. MICRO_SERIES REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.


9 PINS




HERMETIC
FEEDTHROUGH FA41500



HERMETIC SOLDERCUP
FEEDTHROUGH FA42164




PLUG, GARTER TYPE
FA42137




PLUG, SCREW TYPE: FA41506

PRE-WIRED PLUG
-KAPTON: FA42239
-PTFE: FA42419




IN-VAC
RECEPTACLE
FA42394


15 PINS




HERMETIC
FEEDTHROUGH FA42273



HERMETIC SOLDERCUP
FEEDTHROUGH FA42467




PLUG, GARTER TYPE
FA42475




IN-VAC
RECEPTACLE
FA42488

CONTACTS/WIRE




SOCKET CONTACTS
KT41236 (BRASS 125C)
KT41236-02 (TeCu 250C)



WIRE
KAPTON 48": FA42244
KAPTON 96": FA42245
PTFE 48": FA42246-01/09
PTFE 96": FA42247-01/09



CRIMP TOOL
POSITIONER (PIN & SOCKET)
FP41731



CRIMP TOOL
FP41735

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE
SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN
PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE
PROJECTION



TITLE

MICRO SERIES FAMILY



SOLID SEALING
TECHNOLOGY

REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN	DRAWN	HJ	04/09/2021
A2	CW	4/21/2022	AHDWR027-41	INCHES [mm]	ENG APPR.	HJ	05/03/2021

REV. A2

WWW.SOLIDSEALING.COM

SALES DWG NO. MICRO_SERIES REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.