



PLUGS SOLD SEPARATELY:
 -VACUUM SIDE PEEK PLUG FA42809
 -AIR SIDE PLUG KT42854

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500V DC
CURRENT:	2 AMPS
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 15 PIN HD SUB D CONNECTOR				
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	7/12/2021	PART NO. FA42763 REV. A		WWW.SOLIDSEALING.COM
A1	MH	7/22/2021	MPCL473-11D1	ENG APPR.	MH	7/22/2021	SALES DWG NO. FA42763SL REV. A1			

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.