



PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500 V DC
CURRENT:	2 AMPS
TEMPERATURE:	-269°C TO 200°C

REFER TO INSTRUCTION SHEET "NS13605" FOR PLUG ASSEMBLY INSTRUCTIONS.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE <b>15 PIN HD SUB-D VACUUM PLUG</b>			
REV.	APP'D	DATE	SCALE 1.25:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	7/19/2021	PART NO. FA42809 REV. A	WWW.SOLIDSEALING.COM
A2	JF	09/22/2021	MSME0111-11		ENG APPR.	JF	07/20/2021		SALES DWG NO. FA42809SL REV. A2

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**