



PERFORMANCE SPECIFICATIONS	
TRANSMISSION RANGE 80% MIN	0.25 TO 4 MICRONS
PRESSURE	0 PSIG @ 20°C*
TEMPERATURE	-25°C TO 205°C

*FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE SAPPHIRE VIEWPORT IN KF40			
REV.	APP'D	DATE	SCALE 1.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	3/28/2022	PART NO. FA43792 REV. A	WWW.SOLIDSEALING.COM
A2	JF	03/29/2022	VPVD0026-11		ENG APPR.	MH	3/28/2022		SALES DWG NO. FA43792SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.