


PERFORMANCE SPECIFICATIONS	
MAXIMUM TEMPERATURE	205 °C; MAX HEAT RATE: 3 °C/MIN
INDEX OF REFRACTION	1.487

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



THIRD ANGLE PROJECTION
 TITLE
BOROSILICATE GLASS VIEWPORT IN KF25



REV.	APP'D	DATE	SCALE 2.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	CH	5/6/2024
A2	JF	05/15/2024	VPDP0054-13		ENG APPR.	JF	05/14/2024

PART NO. FA49437 REV. A

WWW.SOLIDSEALING.COM
 SALES DWG NO. FA49437SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.