


PART No.	AIR SIDE PLUG
FA49611	NO
KT49611	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	1KV DC
CURRENT:	2 AMPS
PRESSURE:	0 PSIG @ 20°C**
TEMPERATURE WITHOUT PLUG:	-25°C TO 200°C*
TEMPERATURE WITH PLUG:	-25°C TO 75°C

* 2 HOUR BAKEOUT AT 200°C, 150°C CONTINUOUS USE

**FOR INTERNAL PRESSURE 5 TO 100 PSIG
AN OVERPRESSURE RING IS REQUIRED.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE DBL ENDED MICRODOT IN KF25			 SOLID SEALING TECHNOLOGY	
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	4/29/2024	PART NO. FA49611 REV. A		WWW.SOLIDSEALING.COM
A4	JF	02/10/2025	COMC0012-12		ENG APPR.	MH	4/29/2024			SALES DWG NO. FA49611SL REV. A4

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.