



PLUGS SOLD SEPARATELY:
 -PEEK PLUG FA41187 FOR USE ON BOTH SIDES
 -EXTRA CRIMP CONTACTS KT14601

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500V DC
CURRENT:	5 AMPS*
PRESSURE:	0 PSIG @ 20°C**
TEMPERATURE:	-25°C TO 205° C

*CURRENT PER PIN MAX @ 20°C
 (UP TO 20% TOTAL NUMBER OF PINS)

**FOR INTERNAL PRESSURE 5 TO 100 PSIG
 AN OVERPRESSURE RING IS REQUIRED.

<p>PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.</p>				<p>THIRD ANGLE PROJECTION</p> 		<p>TITLE</p> <p>9 PIN SUB-C CONNECTOR</p>				 <p>SOLID SEALING TECHNOLOGY</p>	
REV.	APP'D	DATE	SCALE 3:2	DIMENSIONS IN INCHES [mm]	DRAWN	CH	1/24/2025	PART NO. FA50730 REV. A	WWW.SOLIDSEALING.COM		
A1	JF	01/27/2025	MPCL0697-40		ENG APPR.	JF	01/27/2025		SALES DWG NO. FA50730SL REV. A1		

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.