


PART NO.	AIR SIDE PLUG
FA52392	NO
KT52392	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE	1.5 KV DC
CURRENT	1 AMP
PRESSURE	0 PSIG @20°C*
TEMPERATURE WITHOUT PLUG	-25°C TO 205°C
TEMPERATURE WITH PLUG	-25°C TO 165°C

* FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE
 50 OHM TYPE N TO SMA IN KF25



REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	6/1/2026
A1	MH	6/1/2026	COTN0085-12		ENG APPR.	MH	6/1/2026

PART NO. FA52392 REV. A

WWW.SOLIDSEALING.COM
 SALES DWG NO. FA52392SL REV. A1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.