


+ CONDUCTOR LOCATIONS: A,C,E,G,J  
 - CONDUCTOR LOCATIONS: B,D,F,H,K

PERFORMANCE SPECIFICATIONS	
CONDUCTOR MATERIAL:	(+) CHROMEL / (-) ALUMEL
TEMPERATURE:	-269°C TO 450°C

PLUGS SOLD SEPARATELY:  
 -AIR SIDE PLUG W/CRIMP CONTACTS: FP41398  
 -VACUUM SIDE PEEK PLUG: FA41399

PROPRIETARY AND CONFIDENTIAL  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE  
 5 PAIR TYPE K T/C IN CF2.75



REV.	APP'D	DATE	SCALE 3:2	DIMENSIONS IN INCHES [mm]	DRAWN	JF	04/27/2026
A1	JF	04/27/2026	MPCL0106-12SL		ENG APPR.	JF	04/27/2026

PART NO. FA52550 REV. A

WWW.SOLIDSEALING.COM  
 SALES DWG NO. FA52550SL REV. A1

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**