


RATINGS	
VOLTAGE:	500V DC
CURRENT:	2 AMPS
PRESSURE:	200 PSIG @ 20°C
OPERATING TEMPERATURE:	175°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

BNC TO MICRODOT IN 1" BOLT

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	7/11/2008
A3	JF	03/02/2016	MABP0001-12		ENG APPR.	MH	07/22/2008

PART NO. FP13218 REV. A

SALES DWG NO. FP13218SL REV. A3

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.