



| PERFORMANCE SPECIFICATIONS | |
|----------------------------|----------------|
| VOLTAGE (DWV): | 5KV DC |
| OPERATING VOLTAGE: | 1.5KV DC |
| CURRENT: | 10 AMPS |
| TEMPERATURE: | -65°C TO 165°C |

| | | | | | | | | | | |
|---|-------|------------|-------------|--|-----------|----------------------|------------|-------------------------|---|--|
| PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED. | | | |  THIRD ANGLE PROJECTION | | TITLE HN PLUG | | |  SOLID SEALING TECHNOLOGY | |
| REV. | APP'D | DATE | SCALE 2:1 | DIMENSIONS IN INCHES [mm] | DRAWN | MH | 10/26/2006 | PART NO. FP15700 REV. B | WWW.SOLIDSEALING.COM | |
| B1 | JF | 02/24/2025 | ACNTH007-11 | | ENG APPR. | MH | 10/27/2006 | | SALES DWG NO. FP15700SL REV. B1 | |

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.