



PERFORMANCE SPECIFICATIONS	
TEMPERATURE	-269°C TO 450°C

-TO BE USED WITH COPPER PINCH OFF TUBE
GASKETS FOR 2.75 CF FLANGE

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				 THIRD ANGLE PROJECTION		TITLE 2.75 CF FLANGE			 SOLID SEALING TECHNOLOGY	
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	CH	9/2/2025	PART NO. FP51236 REV. A	WWW.SOLIDSEALING.COM	
A1	JF	09/10/2025	AFLCF008-91		ENG APPR.	JF	09/10/2025		SALES DWG NO. FP51236SL REV. A1	

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.