



PERFORMANCE SPECIFICATIONS	
CURRENT:	25 AMPS
TEMPERATURE:	-200°C TO 200°C

NOTE: PACKAGE OF 10 CONTACTS, 11 SET SCREWS
 (CONTACTS AND SET SCREWS NOT ASSEMBLED)
 -INCLUDES AN L-KEY, STANDARD TIP, 6 FLUTE SPLINE WRENCH
 0.060" DRIVE SIZE, 1-3/4" OVERALL LENGTH

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE PUSH ON CONTACT			
REV.	APP'D	DATE	SCALE 5:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/13/2006	PART NO. KT10903 REV. A WWW.SOLIDSEALING.COM	
A3	JF	08/24/2023	MSCN0002-02		ENG APPR.	MH	03/21/2006		

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.