



RATINGS	
CURRENT:	13 AMPS
TEMPERATURE:	-200°C TO 400°C

NOTE: PACKAGE OF 10 CONTACTS

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. KT11564SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

BARREL CONTACT

PART NO. KT11564 REV. A

REV.	APP'D	DATE	SCALE 6:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/13/2006
A2	JF	12/07/2016	MSCN0001-01		ENG APPR.	MH	03/21/2006

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.