

RATINGS	
CURRENT:	20 AMPS
TEMPERATURE:	-200°C TO 400°C

NOTE: PACKAGE OF 10 CONTACTS

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)




**SOLID SEALING TECHNOLOGY, INC.**

SALES DWG NO. KT11566SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

BARREL CONTACT

PART NO. KT11566 REV. A

REV.	APP'D	DATE	SCALE 6:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	02/15/2006
A2	JF	12/07/2016	MSCN0001-03		ENG APPR.	MH	03/21/2006

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**