



SPECIFICATIONS  
 RATED UL94V-0  
 STEEL SHELL W/ TIN PLATING  
 GLASS FILLED THERMOPLASTIC INSULATOR  
 BLACK PLASTIC HOOD - HINGED W 4-40 THREADED THUMBSCREWS

PERFORMANCE SPECIFICATIONS	
VOLTAGE	500 V DC
CURRENT	5 AMPS
TEMPERATURE	-50°C TO 105°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 	TITLE 50 PIN SUB D AIR SIDE PLUG				
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	05/23/2008	PART NO. KT14879 REV. C	WWW.SOLIDSEALING.COM
C2	JF	07/29/2021	KT14879-11		ENG APPR.	MH	05/23/2008		

***DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.***