


SPECIFICATIONS:
 RATED UL94V-0
 STEEL SHELL W/ NICKEL & TIN PLATING
 THERMOPLASTIC INSULATOR
 GRAY PLASTIC HOOD

PERFORMANCE SPECIFICATIONS	
VOLTAGE	500V DC
CURRENT	2 AMPS
TEMPERATURE	-55°C TO 105°C

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE
 62 PIN SUB D AIR SIDE PLUG



REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	03/16/2008
B2	JF	07/29/2021	ACNMS016-11		ENG APPR.	MH	05/23/2008

PART NO. KT18035 REV. B

WWW.SOLIDSEALING.COM
 SALES DWG NO. KT18035SL REV. B2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.