



RATINGS	
MATERIAL:	BERYLLIUM COPPER
CURRENT:	20 AMPS
TEMPERATURE:	-200°C TO 200°C

NOTE: PACKAGE OF 10 CONTACTS

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. KT18690SL REV. A1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

PUSH ON / CRIMP CONTACT

PART NO. KT18690 REV. A

REV.	APP'D	DATE	SCALE 4:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	08/15/2013
A1	MH	08/15/2013	ACNCT003-02C		ENG APPR.	MH	08/15/2013

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.