



CONTACT MATERIAL:	LOCATIONS:
CHROMEL (+)	A,C,E,G,I
ALUMEL (-)	B,D,F,H,J

PERFORMANCE SPECIFICATIONS	
THERMOCOUPLE	TYPE K
TEMPERATURE:	-55°C TO 125°C

REFER TO INSTRUCTION SHEET "NS19712" FOR PLUG ASSEMBLY INSTRUCTIONS.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 	TITLE TYPE K 5 PAIR AIR SIDE PLUG				
REV.	APP'D	DATE	SCALE 5:4	DIMENSIONS IN INCHES [mm]	DRAWN	JS	10/31/2008	PART NO. KT19713 REV. A	WWW.SOLIDSEALING.COM
A2	JF	06/30/2021	MSME0002-05		ENG APPR.	MH	11/04/2008		SALES DWG NO. KT19713SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.