


-AIR SIDE PLUG INCLUDED

RATINGS	
VOLTAGE:	2.5 KV DC
CURRENT:	200 AMPS
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE WITHOUT PLUG:	-25°C TO 205°C
TEMPERATURE WITH PLUG:	-25°C TO 125°C

\*FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE:  
ONE PIN CONNECTOR



REV.	APP'D	DATE	SCALE 4:5	DIMENSIONS IN INCHES [mm]
A2	JS	11/26/2012	FTCL0140-14	

DRAWN	JS	6/23/2009
ENG APPR.	MH	07/01/2009

PART NO. KT20693 REV. A

SOLID SEALING TECHNOLOGY, INC.  
SALES DWG NO. KT20693SL REV. A2