



PERFORMANCE SPECIFICATIONS	
VOLTAGE:	30KV DC
CURRENT:	10 AMPS
PRESSURE:	400 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-80°C TO 450°C*
TEMPERATURE WITH PLUG:	-55°C TO 125°C

\*CALL SST TO CONFIRM LOWER TEMPERATURE USE

AIR SIDE PLUG/CABLE ASSEMBLY INCLUDED

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE <b>30KV CONNECTOR</b>			
REV.	APP'D	DATE	SCALE 3:2	DIMENSIONS IN INCHES [mm]	DRAWN	JS	01/07/2011	PART NO. KT21997 REV. D	WWW.SOLIDSEALING.COM
D1	JF	05/17/2024	FTCL0130-13		ENG APPR.	JS	07/12/2012		SALES DWG NO. KT21997SL REV. D1

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**