



PART NO.	PLUG INCLUDED
KT35741	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	3KV (WITH PLUG)
CURRENT:	1.0 AMP PER PIN
PRESSURE:	1000 PSIG @ 20 °C
TEMPERATURE WITHOUT PLUG:	*-80 °C TO 450 °C
TEMPERATURE WITH PLUG:	-40 °C TO 105 °C

*CALL SST TO CONFIRM LOWER TEMPERATURE USE

REFER TO INSTRUCTION SHEET "NS28193" FOR PLUG ASSEMBLY INSTRUCTIONS.

REFER TO INSTRUCTION SHEET "NS35741" FOR WELD INSTALLATION INSTRUCTIONS.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				<div>THIRD ANGLE PROJECTION</div> 		TITLE 8 PIN CONNECTOR			 <div>SOLID SEALING TECHNOLOGY</div>			
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	06/12/2018	PART NO. KT35741 REV. B			WWW.SOLIDSEALING.COM	
B2	JF	06/10/2021	MPCL0453-51		ENG APPR.	JF	06/12/2018				SALES DWG NO. KT35741SL REV. B2	

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.