



SPECIFICATIONS:  
 STEEL SHELL W/ NICKEL & TIN PLATING  
 THERMOPLASTIC INSULATOR -RATED UL94V-0  
 BLACK PLASTIC HOOD- RATED UL94HB,  
 HINGED W 4-40 THREADED THUMBSCREWS

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500V DC
CURRENT:	1 AMP
TEMPERATURE:	-55°C TO 105°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 26 HD SUB D AIR SIDE PLUG			
REV.	APP'D	DATE	SCALE 1.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	07/29/2021	PART NO. KT37802 REV. A	WWW.SOLIDSEALING.COM
A1	JF	07/29/2021	KT37802-11		ENG APPR.	JF	07/29/2021		SALES DWG NO. KT37802SL REV. A1

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**