

CRIMP CONTACTS SOLD SEPARATELY

- 12 AWG (20 AMPS) P/N FP39118
- 16 AWG (10 AMP) P/N FP39118-02

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500 V DC
TEMPERATURE:	-269°C TO 200°C

-ALSO AVAILABLE VACUUM SIDE BACKSHELL P/N FA19847

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA39111SL REV. A1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

3 PIN SUB D POWER VACUUM PLUG

PART NO. FA39111 REV. A

REV.	APP'D	DATE	SCALE 1.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	4/16/2019
A1	JF	11/25/2019	MSME0096-11		ENG APPR.	JF	11/25/2019

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.